


適応管サイズ		塩ビ管 VU-150		
流入管底高		槽内底 → 1200H		
流出管底高		槽内底 → 1200H		
有効容量 (m3)	第1槽	0.70 (m3)		
	第2槽	0.70 (m3)		
	第3槽	0.70 (m3)		
	合 計	2.10 (m3)		
重量 (kg)	流入出ユニット		1基	4504
	スラブ版		1枚	729
	合 計	5233 (kg)		
500角铸铁蓋		3枚 (T-25)		
連結用金物類		一式 (プレートボルト・ワッシャ)		
トラップ管		1本 (取付済)		
高さ調整桟		別途協議 (要・不要・指定H)		

吊り金具・施工治具
詳細は別途「施工用道具説明書」をご確認ください

コーキング	コーキング 剤4本・コーキング ガン
玉掛け用具	ワイヤー・シャックル

Technical drawing of the T-25 cast iron cover (T-25鑄鐵蓋) showing dimensions and layout. The cover is rectangular with a total width of 2240 and a total height of 395. It features three square openings, each 450 wide and 450 high, spaced 250 apart. The cover is made of T-25 cast iron.

流入管接続（現場手配）



流出管接続

[illegible]

Technical drawing of the front view of a rectangular unit. The overall dimensions are 2240 (width) and 1815 (height). The drawing includes the following dimensions and labels:

- Dimensions:**
 - Overall width: 2240
 - Overall height: 1815
 - Top flange thickness: 140
 - Internal vertical distance from top flange to main body: 350
 - Main body height: 1550
 - Bottom flange thickness: 125
 - Internal vertical distance from main body to bottom flange: 1200
 - Bottom flange width segments: 120, 600, 100, 600, 100, 600, 120
 - Right side flange thickness: 490
- Labels:**
 - 削孔のみ (Only chamfered holes)
 - 塩ビ管別途 (PVC pipe sold separately)
 - 流出管 (Outlet pipe)
 - 管取付済 (Pipe installed)

[illegible]

Technical drawing of a rectangular box with the following dimensions:

- Overall width: 1240
- Overall height: 1815
- Top flange height: 140
- Side panel height: 350
- Internal height: 1550
- Internal width: 1200
- Bottom flange height: 125
- Internal width of the lower section: 1000
- Width of the lower section: 120 (on each side)
- Width of the lower section: 300
- Width of the lower section: 200 (on each side)

花沢建材工業株式会社

油水分離槽 AQS-101815

1 / 35

Figure No

2206-2026

圖 製